

Application: This cable was specifically developed for the EMC-compliant connection of frequency converters. For uses with medium mechanical strain with permanent installation and occasional motion indoors and outdoors, but not in the ground. The version with the three-stranded protective conductor is thinner, lighter and distinguished by improved EMC-properties. The cable is largely oil-resistant.

Construction and technical data:

Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	polyethylene
Screen:	aluminium foil + tinned copper braid
Screen coverage:	75 %
Sheathing material:	PVC, enforced
Colour of outer sheath:	black
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
UV-resistant:	yes
Oil-resistant:	EN 60811-404
For outdoor use:	yes
Max. temperature at conductor, °C:	70 °C
Permitted outer cable temperature, fixed, °C:	-30 - +70 °C
Permitted outer cable temperature, moved, °C:	-5 - +70 °C
Transfer impedance:	250 Ohm/km



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

Bending radius acc. DIN EN 50565-1

application	<12 mm	12-20 mm	>20 mm
fixed installation	5D	7.5D	10D
free movement	10D	15D	20D