



MOTOR DATA SHEET

MOTOR PART CODE:

18.523EXTDB3

FRAME SIZE:

160L-2

	50Hz
Output (kW)	18.5
Rotation Speed (rpm)	2930
Voltage	400/690
Full Load Current (A)	32.28 18.64
Full Load Torque (Nm)	60.29863481

	60Hz
Output (kW)	22.2
Rotation Speed (rpm)	3516
Voltage	480 828
Full Load Current (A)	32.28 18.64
Full Load Torque (Nm)	50.25

Efficiency Data

100%	75%	50%
90.9	91.5	90.9

Factory Reference	MS2 160L-2
Tst/Tn (times)	3.2
Tmax/Tn	3.2
Noise (dB)	86
Moment of inertia	0.06880666
Type of feet	Removable feet
Protection	IP65
Rotation Direction	F / R
Cable Glands	2 - M32 × 1.5
Paint Colour	RAL 7024
ATEX	ATEX II 3D Ex tc IIIC T125°C - Dc
Bearing (DE)	6309 2RS C3

Power Factor (cos)	0.91
Tmin/Tn	2.2
Ist/In (Times)	9
Net Weight (Kg)	102.5
Housing material	Aluminum
Insulation Class	F
Thermal Protection	PTC 130°C
Duty Cycle	S1
Cooling	IC411
Ambient Temperature	-20°C to + 40°C
Bearing Brand	NSK
Bearing (NDE)	6309 2RS C3

Motors designed and manufactured in accordance with:



IEC 60034
IEC 60038
IEC 60072
IEC 60079
2014/35/EU (LVD)
2011/65/EU (RoHS 2)

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information