

PST300-600-70



Products Low Voltage Products and Systems Control Products Softstarters Softstarters

General Information

Extended Product Type:	PST300-600-70
Product ID:	1SFA894014R7000
EAN:	7320500255629
Catalog Description:	PST300-600-70 SOFTSTARTER
Long Description:	Softstarter PST300-600-70 for max 600V main voltage and 110 - 240V 50/60Hz control supply voltage

Interactive Guides

Category Related Guides:

ABB improves mining industry efficiency - Softstarter PSTX

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85371099
EAN:	7320500255629

Dimensions

Product Net Height:	420.000 mm
Product Net Depth:	270.000 mm
Product Net Weight:	23 kg
Product Net Width:	360.000 mm

Container Information

Package Level 1 Length:	475 mm
Package Level 1 Height:	310 mm
Package Level 1 Gross Weight:	24.6 kg
Package Level 1 EAN:	7320500255629
Package Level 1 Units:	1 piece
Package Level 2 Units:	1 piece
Package Level 1 Width:	400 mm

Technical

Rated Control Supply Voltage (U_s):	100 ... 250 V AC
Rated Control Circuit Voltage (U_c):	DC Operation 24 V
Rated Frequency (f):	Main Circuit 50/60 Hz Control Supply 50/60 Hz
Rated Operational Power - In-Line Connection (P_e):	at 400 V 160 kW at 500 V 200 kW
Rated Operational Current - In-Line Connection (I_e):	300 A
Rated Operational Power - Inside Delta Connection:	at 400 V 257 kW at 500 V 355 kW
Rated Operational Current - Inside Delta Connection:	515 A
Service Factor Percentage:	115 %
Overload Protection:	Build-in electronic overload protection
Integrated Electronic Overload:	Yes
Adjustable Rated Motor Current I_e:	30 ... 115 %
Starting Capacity at Maximum Rated Current I_e:	3xI _e for 15s
Ramp Time:	During Start 1 ... 30 second(s)

During Start 1 ... 120 second(s)
During Stop 0 ... 30 second(s)
During Stop 0 ... 120 second(s)

Initial Voltage During Start:	30 ... 70 %
Step Down Voltage Special Ramp:	100...30 %
Current Limit Function:	1.5 ... 7xI _e
Switch for Inside Delta Connection:	Yes
Run Signal Relay:	Yes
By-pass Signal Relay:	Yes
Fault Signal Relay:	Yes
Overload Signal Relay:	Yes
Analog Outputs:	0...10 volts 0...20 mA 4...20 mA
Signal indication ready to start/standby ON (LED):	Green
Signal indication protection (LED):	Yellow
Signal indication fault (LED):	Red
Number of Starts Per Hour at 3.5*I_e for 7 sec. 50%ON Time 50%OFF Time:	30
Communication:	FieldBusPlug(Standard)
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type:	Main Circuit: Bars
Connecting Capacity Main Circuit:	Hole Diameter 10.2 mm Width and Thickness 20x5 mm
Connecting Capacity Control Circuit:	Rigid 1x2.5 mm ² Rigid 2x1.5 mm ²
Connecting Capacity Supply Circuit:	Rigid 1x2.5 mm ² Rigid 2x1.5 mm ²
Tightening Torque:	Main Circuit 28 N·m Supply Circuit 0.5 N·m Control Circuit 0.5 N·m
Product Main Type:	PST300
Rated Operational Voltage:	Main Circuit 208 ... 600 V AC

Environmental

Ambient Air Temperature:	Operation 0 ... +50 °C Storage -25 ... +70 °C
Battery Information:	Button Cell Yes Contains Cd <0.01 % Contains Hg <0.01 % Contains Pb <0.01 % Type Portable Weight 0.0031 kg
RoHS Status:	No declaration needed

Certificates and Declarations (Document Number)

Instructions and Manuals:	1SFC132003M0201
Data Sheet, Technical Information:	1SFC132005C0201
Declaration of Conformity - CE:	1SFA1-74
RoHS Information:	1SFC132035D0201

Classifications

E-number:	3302163
ETIM 4:	EC002572 - Electronic motor control and protection device
ETIM 5:	EC002572 - Electronic motor control and protection device

UNSPSC:

39121521

Object Classification Code:

Q

