Connection cable M12, 8-pin, angled, shielded



Features

- Connection cable shielded with female connector M12, shielding on cap nut
- 8-pin version
- Cable coating PUR
- Halogen-free
- Suitable for flexible cable carriers
- UL listed, number E315836
- Temperature -40...+80 °C (fixed installation)

Part number		
11053961	Connection cable 2 m shielded with female connector M12, 8-pin, angled (ESW 33FH0200G)	
11053962	Connection cable 5 m shielded with female connector M12, 8-pin, angled (ESW 33FH0500G)	
10170054	Connection cable 10 m shielded with female connector M12, 8-pin, angled (ESW 33FH1000G)	


Suitable for

EIL580 - blind hollow shaft, EIL580 - clamping flange, EIL580 - synchro flange, EIL580 - through hollow shaft, EIL580P - blind hollow shaft, EIL580P - clamping flange, EIL580P - synchro flange, EIL580P - through hollow shaft

Terminal assignment			
Female connector M12	Core colour		
Pin 1	white		
Pin 2	brown		
Pin 3	green		
Pin 4	yellow		
Pin 5	grey		
Pin 6	pink		
Pin 7	blue		
Pin 8	red		
Connnector Housing	Shield/Housing		



Dimensions



Dimension

EIL580 - Cable outlet connection cable M12 angled

