



B5, V1, V3	Flansch / Flange	a1	b1	c1	e1	f1	s1
	A250	250	180	13	215	4	14
B14, V18, V19	C160	160	110	-	130	3,5	M8
	C200	200	130	-	165	4	M10

Selbsterregten Motoren / self excited motors

Typ / Type	Spannung V /	Nennleis-	Drehzahl	Nennstrom A /	Mass.trägh.mom.	Kohlebürsten /		
		tung kW /	min ⁻¹ /		kgm ² · 10 ⁴ /	Carbon brushes		
	Voltage V	Nominal output kW	Speed rpm	Rated current A	Mass moments of inertia kgm ² · 10 ⁴	Abm. / Dim.	Qual. / Qty.	Anz. / Qty.
100S-4GM ^c	12	0,55	1500	63	39	10X20X20	MK55	4
100M-4GM ^c	12	0,75	1500	86	45	10X20X20	MK56	4
100S-4GM ^c	12	0,75	3000	89	39	10X20X20	MK57	4
100M-4GM ^c	24	0,75	1500	46	45	10X20X20	MK58	4
100L-4GM ^c	24	1,1	1500	62	57	10X20X20	MK59	4
100M-4GM ^c	24	1,1	3000	65	45	10X20X20	MK60	4
100L-4GM ^c	24	1,5	3000	82	57	10X20X20	MK61	4
100L-4GM ^c	110	1,3	1500	15,5	53	8X20X20	EG98	4
100L-4GM ^c	110	2,6	3000	30,5	53	8X20X20	EG98	4
100L-4GM ^c	220	1,3	1500	8,0	53	8X20X20	EG98	4
100L-4GM ^c	220	2,6	3000	15,5	53	8X20X20	EG98	4
^c Doppelschluß; Nebenschluß auf Anfrage / compound; shunt on demand								

Fremderregten Motoren / separate excited motors

[illegible]