



131B7582 🕑

FC-102P45KT4E55H3XGX1XXSXXXAXBXCXXXXDXFrequency ConverterFC-102P45KT4E55H3XGX1XXSXXXAXBXCXXXXDXVLT* HVAC Drive FC-102(P45K) 45 KW / 60 HP, Three phase380 - 480 VAC, IP55 / Type 12(H3) RFI Class A1/B (C1)No brake chopperGraphical Loc. Cont. PanelNot coated PCB, Mains DisconnectLatest release std. SW.Frame: C1No C1 option, No D optionNo A Option, No B OptionOther options according to Model Code

Model code: FC-102P45KT4E55H3XGX1XXSXXXAXBXCXXXDX

Danfoss Drive is dedicated to ventilation, heating, and refrigeration applications. With a wide range of powerful standard and optional features, the Drive provides the lowest overall cost of ownership.

View Efficiency Data 🛽

PRODUCT DETAILS

Gross weight		43.12 kg
Net weight		41.92 kg
Volume		188.191
EAN		5702427358355
Sales restriction control		
Matr grp for sales restriction	0001	No grouping
VLT® HVAC DRIVE FC 100 SERIES		
Product View (Switch)	GLBL	Global (Standard)
Product Group	FC-	VLT® HVAC Drive FC-
Series	102	102
Power Rating	P45K	(P45K) 45 KW / 60 HP
Phase	Т	Three phase
Mains Voltage	4	380 - 480 VAC
Enclosure	E55	IP55 / Type 12
RFI Filter	H3	(H3) RFI Class A1/B (C1)
Brake - Safe Stop	Х	No brake chopper
LCP	G	Graphical Loc. Cont. Panel
Coating PCB	Х	Not coated PCB
Mains Option	1	Mains Disconnect
Adaptation A	Х	Standard Cable Entries
Adaptation B	Х	No adaptation
Software Release	SXXX	Latest release std. SW.
Software Language Pack	Х	Standard Language Pack
A Option	AX	No A Option
B Option	BX	No B Option

PRODUCT DETAILS

C0 Option MCO	СХ	No C0 option
C1 Option	Х	No C1 option
C Option Software	XX	No software option
D Option	DX	No D option
Frame Size	C1	C1
Product Catalog	NO_VIEW	NO VIEW
Typecode Part 1		FC-102P45KT4E55H3XGX
Typecode Part 2		1XXSXXXAXBXCXXXXDX
Power 110% (NO) [KW]		45
Height [mm]		680,0
Width w/ no C options [mm]		308,0
Depth [mm]		310,0
Depth with Option A/B [mm]		310,0
kVA		62.4
Power Loss NO [W]		843
Power Loss NO [W]		843
Continuous Current (NO) [A]		90
Intermittent Current (NO) [A]		99
Continuous Current (NO) [A]		80
Intermittent Current (NO) [A]		88
Calculated Gross Weight [kg]		41.3
Calculated Net Weight [kg]		41
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Modelcode01		FC-102P45KT4E55H3XGX
Modelcode02		1XXSXXXAXBXCXXXXDX

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🗈

Accessories

130B4597 🛽

Weather shield f. outdoor instl. C1, C2 Weather shield for enclosure sizes C1, C2



130B3910 🖻

Back plate IP21/Type 1, IP55/Type 12, C1 FC 300 back cover for the devices in IP21 / 55 Case size C1



130B7533 🛛

Mounting Kit C Option, B/C/D/E/F(not B3) MCF105 C Option, Mounting Kit A2 and A3

For more information, please use this link to visit the product page on Danfoss Product Store 🗅



areau And and and and and and and and and and a	 130B5436 ₽ Side Fixture Mounting Kit Side Fixture Mounting Kit for enclosure size A5 / B1 / B2 / C1 / C2 To be used when retrofitting the following MCA options: MCA 120 Profinet MCA 121 EtherNet MCA 122 Modbus TCP MCA 123 POWERLINK MCA 124 EtherCAT Product group: R1
and the second s	130B5435 I2 DIN Rail Mounting Kit
	130B1170 ট LCP Panel Mounting Kit The kit includes fasteners and gasket. No LCP and no cable included.
	130B1387 ☑ 5xMCB107 24VDC no coat w.out mount brack
	130B1385 ☑ VLT® Profibus DP V1 MCA101, unctd 5pcs
	130B1001 ☑ VLT® Motion Ctrl Tool MCT 10,5 lic. An interactive tool for quick and easy online/offline configuration of a VLT® drive or soft starter using a PC. Configure communication networks and back up relevant parameter settings. Control and configure systems simultaneously and monitor entire system more effectively for faster monitoring, diagnosis, troubleshooting (alarms/warnings) and better preventive maintenance.
	 130B1135 ☑ VLT® PROFINET MCA 120, UNCOATED MCA 120 PROFINET interface Supports operation on PROFINET network with extensive properties DCP support for easy setting u. Communication parameters via the PLC On Board web-Page with Drive Status Parameterization with the MCT10 software 2 port version, reduced external hardware

For more information, please use this link to visit the product page on Danfoss Product Store 🗈





130B1125 🛛

VLT® General Purpose I/O MCB 101, unctd

MCB 101 - Advanced I / O option Expands the number of freely programmable Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 24 V.
- 2 analog inputs 0 10 V.
- 2 digital outputs NPN / PNP switchable 24 V
- 1 analog output 0/4 20 mA



130B1124 🕑

VLT® Control Panel LCP 101, numeric

Numerical control unit for FC 100 and FC 300. Allows access to all device parameters. Quick menu for brief commissioning. Manual / auto switchover and alarm acknowledgment.



130B1117 🗅

LCP Mounting Kit, w/ no LCP The kit includes fasteners, 3m cable and gasket - There is no LCP included.



130B1110 🛛

VLT° Relay Option MCB 105, uncoated Relay extension for FC 100 and FC 300. Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology. Max. Load 240V AC (resistive): 2 A Max. Load 240V AC (Cos Phi 0.4): 0.2 A Max. Load 24V DC (ohmic): 1 A Max. Load 24V DC (inductive): 0.1 A



130B1156 🛛

USB extension Cable, 650mm

USB extension kit for FC 300 cable length: 650mm for the housing size: B2, C1 and C2 screw connection M 25 $\,$



130B1143 🕑

VLT[®] Analog I/O Option MCB 109, unctd I / O expansion for FC 100, through modular technology easy to retrofit. Analog inputs/outputs galvanically isolated. Expands the analog inputs / outputs by: 3 analog inputs: 0 ... 10V / Pt1000 / Ni1000 3 analog outputs: 0 ... 10V Time switch (RTC backup): lithium cell for 10 years



130B1083 🛛

Mounting Brackets, C1 Mounting brackets for enclosure size C1

For more information, please use this link to visit the product page on Danfoss Product Store 🗷

ENGINEERING TOMORROW



Accessories

130B1077 🖄

Blindcover, w/ Danfoss logo, IP55/66 LCP Blindcover IP66



130B1070 🖻

RS485 plug, FC series, 10 pcs 10pcs RS485 connectors for FC-series. Product group: R



130B1108 🗠

VLT® 24V DC Supply MCB 107, uncoated

Connect an external DC supply to keep the control section and any installed option alive during power failure. Enables full operation of the LCP (including the parameter setting) and all installed options without connection to mains.



130B1102 🗅

VLT® DeviceNet MCA 104, uncoated

Robust, efficient data handling thanks to advanced Producer/Consumer technology. ODVA's strong conformance testing policies ensure products are interoperable, and the AC-drive profile, supported using I/O instance 20/70.21/71, secures compatibility to existing systems.



130B1100 🛛

VLT® Profibus DP V1 MCA 101

Provides wide compatibility, a high level of availability, support for all major PLC vendors and compatibility with future versions. Fast, efficient communication, transparent installation, advanced diagnosis and parameterization and auto-configuration of process data using GSDfile. Acyclic parameterization using PROFIBUS DP-V1, ¬PROFIdrive or Danfoss FC profile state machines, PROFIBUS DP-V1, Master Class 1 and 2.



175Z0929 🛛

LCP Cable, 3m

Cable for control panel (LCP), 3 meters Works with the following LCP: Alphanumeric control panel LCP3 - 175N0131 VLT® LCP 102 Graphic Display - 130B1107 VLT® LCP 101 Numeric Display - 130B1124 VLT® LCP 102 Graphic display IP66 - 130B1078 Product group: F1

Image coming soon

175U0009 🕑

Mounting bracket Kit, 216 x 30 x 18mm Mounting angle for flatpack resistor 200W

For more information, please use this link to visit the product page on Danfoss Product Store 🗷







175N2584 🖻

VLT® EtherNet/IP Modbus TCP gateway

134B5925 🛛
Pressure Transmitter

VLT PTU 025 pressure transmitter unit for external attachment to frequency converters VLT HVAC Drive FC-102 IP55 / IP66 on one the cable entries suitable for M25 - with four pressure sensors 2x 0-500 Pa; 1x 0-1000 Pa; 1x 0-2500 Pa - eight hose connections D 5mm - Can be positioned 360 ° around the longitudinal axis Software version of the frequency converter FC-102 at least 5.20 am required Mounting thread: M25 Dimensions LxW: 155mm x 38mm (Length with hose support rail 260.5mm) Degree of protection: IP66

Image coming soon

134B5225 Remote LCP unit, 10m

Remote mounting kit for LCP with cover for outdoor mounting with 10 m (33 ft) cable

Image coming soon

134B5224 🛽

Remote LCP unit, 5m Remote mounting kit for LCP with cover for outdoor mounting with 5 m (16 ft) cable



134B5223 🕑

Remote LCP unit, 3m Remote mounting kit for LCP with cover for outdoor mounting with 3 m (10 ft) cable

For more information, please use this link to visit the product page on Danfoss Product Store 🗷





134B0460 🕑

LCP 103 Wireless Communication Panel
With VLT® Wireless Communication Panel LCP 103 you can communicate with
MyDrive® Connect - an app that can be downloaded for iOS and Android
based smartphones. MyDrive® Connect makes commissioning easy,
monitor and maintain tasks on your frequency converter. VLT® Wireless
Communication Panel LCP 103 shows the current status of the drive (On,
Warning, Alarm, Wifi connection) via built-in LED. Detailed
information is also available using MyDrive® Connect. Here
do you have access to i.a. status, menu and alerts. You can also see graphs
over the latest available data.
The new VLT® Wireless Communication Panel LCP 103 allows you to
wireless communication to the following drives:
- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® AQUA Drive FC 202
- VLT® AutomationDrive FC 302
[!] Note!
LCP 103 only works on frequency converters produced in 2018 (White USB
stik).
Product group: R1

Image coming soon

Image coming soon

130B6447 🛽

134B1992 🕑

VLT[®] Safety Option MCB 141

Control Terminals w/ screw connections

Extends the Safe Torque Off feature of VLT® drives with additional safety functions: Safe Stop 1 (SS1), Safely Limited Speed (SLS), Safe Maximum Speed (SMS) and Safe Speed Monitor (SSM).



130B1106 🗠

VLT® LonWorks MCA 108, uncoated

Developed for building automation, it enables communication between individual units in the same system (peer-to-peer) and supports decentralizing of control. No need for main station (master-follower). Units receive signals directly. Supports Echelon free-topology interface (flexible cabling and installation) and embedded I/Os and I/O options (easy implementation of decentral I/Os). Sensor signals can quickly be moved to another controller using bus cables. Certified as compliant with LonMark ver. 3.4 specifications.

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Accessories

HI II	 130B1144 ☑ VLT* BACnet MCA 109, uncoated Open communication protocol dedicated to building automation Efficient integration of all parts of building automation equipment BACnet: standard for building automation worldwide International standard ISO 16484-5 can be used in all sizes of building automation systems the Drive communicates easily with construction management systems running the BACnet protocol can be easily integrated into the network of existing control equipment Product group: R1
lmage coming soon	134B7207 cable clamp/d=44-48 k48b
Image coming soon	134B7209 ⊠ cable clamp/d=36-40 k40b
	130B0295 🖻 Accessory bag with control card plugs
lmage coming soon	134B1968 Accessory bag for frame size C1 Accessory bag for frame size C1
	134B1586 ☑ VLT® BACNET/IP MCA125 The VLT® BACNET/IP MCA 125 option is a plug-and-play solution that optimizes the use of VLT® HVAC Drive together with building management systems using the BACnet/IP protocol or running BACnet on Ethernet. The embedded three-port managed switch of the VLT® BACnet/IP MCA 125 option comprises two external and one internal Ethernet port. This switch allows the use of line structure for the Ethernet cabling. In modern installation this is becoming increasingly attractive
lmage coming soon	130B4847 🖻 extension cable for lcp+communication
	134B8492 🗷 Transducer 0-10g, 4-20mA; HS-22B50

For more information, please use this link to visit the product page on Danfoss Product Store f Z

ENGINEERING TOMORROW



134B8493 ☑ CBM Transducer 0-25mm/s RMS 4-20mA	
CBM Transducer 0-25mm/s RMS 4-20mA	
CBM Transducer 0-25mm/s RMS 4-20mA	
134B8494 🗠	
Transducer w, temp 0-25mm/s RMS 4-20mA	
134B8496 ⊠	
Cable assy 10m, straight socket connetc.	
134B8497 ⊵	
Cable assy, M12 female connec.10m screen	
134B7466 ⊵	
Option A Ethernet Package	
612Z1182 ⊠	
fuse,4a,3 x 32mm,super fast	
130B3273 ⊠	
c1 cover with gasket	
130B9977 ⊠	
Cable kit, C1	
130B9976 ⊠	
Cable assy for motor cables, C1	
	Transducer w, temp 0-25mm/s RMS 4-20mA 134B8496 (2) Cable assy 10m, straight socket connetc. 134B8497 (2) Cable assy, M12 female connec.10m screen 134B7466 (2) Option A Ethernet Package 612Z1182 (2) fuse,4a,3 x 32mm,super fast 130B3273 (2) c1 cover with gasket 130B9977 (2) Cable kit, C1

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

ENGINEERING TOMORROW



e Parts	
(G	130B9975 🗹 Motor Cable assembly with RFI Core
x10	130B9001 I2 multiple 2 pole power combicon, 24V plug
	130B1054 년 Mains switch 100A
	130B1036 ⊠ DC coil 45kW T4/6 and 22kW T2
	130B1032 🛙 Mains switch 125A
	130B0264 ☑ Cradle for A5,B1,B2,C1,C2,D2h enclosure cradle for LCP cradle for a5, b1,b2,c1,
	130B0295 🖻 Accessory bag with control card plugs
	130B1077 ট Blindcover, w/ Danfoss logo, IP55/66 LCP Blindcover IP66
2000 2000	130B1069 ≥ Multiple relay 1 plug spare, 3 pole connector, relay 1, fc300
4451 8883 8 8	130B1068 ⊠ Multiple relay 2 plug spare, 3 pole connector, relay 2, fc300

For more information, please use this link to visit the product page on Danfoss Product Store 🗈



Spare	Parts	

	130B1107 🖻
346	VLT° Control Panel LCP 102
	Graphic operating unit LCP102 Illuminated graphic display with plain
	text. Supports all languages and characters. Quick menu for brief
	commissioning.Saving and copying parameter sets.Online help for each
	function
	130B1086 🖻
\$	Handle and gasket for mains switch
0000	Handle and gasket for mains switch
	130B1828 ⊠
AT IN A	Power Card 45kW 400V
	130B1894 ⊵
Alter .	Cur. trans.card 500V frame C1/C3/H7/I7
	For devices manufactured before week 6, 2010, purchase of busbar
	130B9977 is additionally required.
	130B1887 🗠
	Inrush SCR/Diode Module 1600V 106A
	130B1884 ⊵
	Dual IGBT Module 1200V 150A
	OBS: 3 pcs are used in each drive
[<u>indinalnul</u> 130B1884	Obs: 5 pcs are used in each drive
	134B1730 ⊠
A CONTRACT OF	Control Card w/o safe stop for FC-102
Trans	NOTE:
	The MKII control cards are backward compatible to the old cards but will only work with SW equal or
	higher than 5.21. If your drive has a customer specific software or a brand labeled software
	version please order the old control card MKI, PN: 130B1151
	134B1968 ⊠
Image	Accessory bag for frame size C1
coming soon	Accessory bag for frame size C1
•	134B1878 🗠
	134B1878 ⊠ capacitor 4500uF 20% 20% 450V

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

ENGINEERING TOMORROW



	132Z0050 ₪	
8	FC102-302 Maintenance package C1	
	1 Qty 134B6862 Fan assembly 172x150x51 mm IP21/54/55	
	1 Qty 134B6863 Fan assembly 60x60x25 mm trans.card C1/2	
	1 Qty 134B6864 Fan assembly 60x60x25 mm power card C1/2	
Image	134B6862 🖻	
Image coming	Fan assembly 172x150x51mm IP21,55	
soon	Ext. Fan assembly 172x150x51 mm for C1	
	132Z0106 ⊠	
122	FC102 St.Spare PKG w/o s. stop 45kW T4C1	
st 1	1 Qty 130B1828 Power Card 45kW 400V	
	3 Qty 130B1887 Inrush SCR/Diode Module 1600V 106A	
	1 Qty 134B7153 BUSBAR KIT FOR RECTIFICER IN FRAME C1	
	1 Qty 134B1730 Control Card w/o safe stop for FC-102	
	132Z0108 🗠	
	FC102 Adv.Spare PKG w/o s.stop 45kW T4C1	
1 The second sec	1 Qty 130B1828 Power Card 45kW 400V	
	3 Qty 130B1887 Inrush SCR/Diode Module 1600V 106A	
	1 Qty 134B7153 BUSBAR KIT FOR RECTIFICER IN FRAME C1	
	1 Qty 134B1730 Control Card w/o safe stop for FC-102	
	3 Qty 130B1884 Dual IGBT Module 1200V 150A	
	1 Qty 134B7151 BUSBAR KIT FOR INVERTER IN FRAMESIZE C1	
	134B7151 ⊵	
3.5 B.	Busbar kit for inverter in framesize C1	
	Busbar kit for inverter in framesize C1 Busbar kit for inverter in framesize C1	
	Busbar kit for inverter in framesize C1	
	134B7153 ⊠	
	Busbar kit for rectificer in frame C1	
	Busbar kit for rectificer in frame C1	
	12407155 (2	
	134B7155 ☑ "Do it yourself" Glanding pl. IP21/55 C1	
The second secon		
	134B7157 ⊠	
	Gasket for glanding plate for frame C1	

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

ENGINEERING TOMORROW



	134B7172 전 Gasket for local control panel IP55/66
	134B7203 고 Terminal blocks 50mm2 screw/screw
lmage coming soon	134B7193 업 cable clamp
0 0 0	134B7202 🗠 Terminal blocks 50mm2 screw Terminal blocks 50mm2 screw
lmage coming soon	134B7184 🖻 Cable assembly for brake cables frame C1
lmage coming soon	134B7182 업 Cable assembly for DC choke frame C1, I7
-	134B7178 ☑ 24 pole 3 connector jumper for C option 24 pole 3 connector jumper for C option
lmage coming soon	134B6863 ☑ Fan assembly 60x60x25mm trans.card C1,C2 Note: Old material number 130B3923
lmage coming soon	134B6864 교 Fan assembly 60x60x25mm Power card C1,C2 Note: Old material number 130B3925
lmage coming soon	134B7057 2 Screws 12 pcs 640f0774 cover B1 B2 C1 C2

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

ENGINEERING TOMORROW



	134B5474 ☑ cable jumper/cable jumper 44 pole c1-2 cable jumper/cable jumper 44 pole c1-2
lmage coming soon	134B5998 🗷 24 pole jumper/2 connector jumper
~))	134B7466 🗷 Option A Ethernet Package
	134B9143 2 RFI unit 200/500V std. A1 for frame C1
100 60 C	130B1071 ≥ 6 Pole Connector, FC series,10 pcs 6-pole spring cage connectors 10 pcs

Services



131H3163 🛛

FC-102P55KT4E55H1UGCXXXSXXXAXBXCXXXXDX Frequency Converter FC-102P55KT4E55H1UGCXXXSXXXAXBXCXXXXDX VLT® HVAC Drive FC-102 (P55K) 55 KW / 75 HP, Three phase 380 - 480 VAC, IP55 / Type 12 (H1) RFI Class A1/B (C1) Brake chopper + Safe stop Graphical Loc. Cont. Panel Coated PCB, No Mains Option Latest release std. SW. Frame: C1 No C1 option, No D option No A Option, No B Option Other options according to Model Code

Model code: FC-102P55KT4E55H1UGCXXXSXXXAXBXCXXXDX

Danfoss Drive is dedicated to ventilation, heating, and refrigeration applications. With a wide range of powerful standard and optional features, the Drive provides the lowest overall cost of ownership.

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Services

 130R1140 ☑ DrivePro ExWarr Work Shop PG05 24 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1141 DrivePro ExWarr Work Shop PG05 30 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1142 ☑ DrivePro ExWarr Work Shop PG05 36 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1144 ☑ DrivePro ExWarr Work Shop PG05 48 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1145 ☑ DrivePro ExWarr Work Shop PG05 54 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1143 ▷ DrivePro ExWarr Work Shop PG05 42 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store 🗹 👘

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Services

 130R1147 ☑ DrivePro ExWarr Work Shop PG05 66 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1148 ☑ DrivePro ExWarr Work Shop PG05 72 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1146 DrivePro ExWarr Work Shop PG05 60 months DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1044 ☑ DrivePro ExWarr Onsite PG05 48 months DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1045 DrivePro ExWarr Onsite PG05 54 months DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
 130R1042 ≥ DrivePro ExWarr Onsite PG05 36 months DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store 🗈



Services

 130R1043 ☑ DrivePro ExWarr Onsite PG05 42 months DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1048 DrivePro ExWarr Onsite PG05 72 months DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1047 ≥ DrivePro ExWarr Onsite PG05 66 months DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1041 Z DrivePro ExWarr Onsite PG05 30 months DrivePro [®] On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro [®] Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1040 DrivePro ExWarr Onsite PG05 24 months DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.
130R1046 DrivePro ExWarr Onsite PG05 60 months DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site. You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store 🗈



DrivePro*Start-up	130R1325 ☑ DriveProStart-UP ctrl. IFT test medium DrivePro Start-Up Control interface testing medium frame unit
DrivePro" Start up	130R1322 ⊵ DrivePro Start-Up special applic. medium DrivePro Start-Up special applications medium frame unit
DirePor Start up	 130R1305 ⊭ DrivePro Start-Up unit pre-order medium DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one. The following benefits can be gained: Installation is checked to ensure it complies to Danfoss guide lines. The AC drive is fine-tuned specific to the application, ensuring optimal performance. Maximum energy savings to the Customer. Extend the AC drive's lifespan. Report detailing findings. Before DrivePro® Start-up can be implemented, the AC drive must be installed and ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

Image coming soon

Services

130R1348 🛛

DrivePro Remote Monitoring - Annual Fee

For more information, please use this link to visit the product page on Danfoss Product Store 🗈