


# TECHNICAL DATA

Three Phase Electric Motors - Cast Iron Frame  
UM3C 200LX-4 IE3  
30 kW / 40 Cv  
1480 RPM



|                             |                  |
|-----------------------------|------------------|
| Motor type:                 | UM3C 200LX-4 IE3 |
| Output:                     | 30 kW / 40 Cv    |
| Speed (min <sup>-1</sup> ): | 1480 RPM         |
| Voltage:                    | 400 V            |
| Frequency:                  | 50 Hz            |
| Current:                    | 53.8 A           |
| Power factor (Cos Ø):       | 0.86             |
| Poles:                      | 4                |
| Insulation class:           | F                |
| Temperature rise Class:     | B                |
| Efficiency 50%:             | 92.4 %           |
| Efficiency 75%:             | 93.4 %           |
| Efficiency 100%:            | 93.6 %           |
| Torque:                     | 194 N.m          |
| Tstarting/Tnominal:         | 2.0              |
| Istarting/Inominal:         | 7.8              |
| Tmaximum/Tnominal:          | 2.3              |
| Noise:                      | 76 Db(A)         |
| Weight:                     | 279 Kg           |
| Bearing DE:                 | 6312 C3          |
| Bearing NDE:                | 6312 C3          |

Regime - S1

Altitude - 1000m

Environment Temperature - 40°C

## CONTACTS:

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Industrial Estate, Meltham Mills Road, Meltham, Holmfirth  
West Yorkshire HD9 4AR, U.K.

Tel: +44(0) 1484 660 222  
Fax: +44(0) 1484 660 333  
Mail: [enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)

\* References applied only in the UK