
TECHNICAL DATA

Three Phase Electric Motors - Aluminum Frame
UMHA 63K-4
0.12 kW / 0.16 Cv
1380 RPM



Motor type:	**UMHA 63K-4**
Output:	**0.12 kW / 0.16 Cv**
Speed (min^{-1}):	**1380 RPM**
Voltage:	**400 V**
Frequency:	**50 Hz**
Current:	**0.5 A**
Power factor (Cos Ø):	**0.54**
Poles:	**4**
Insulation class:	**F**
Temperature rise Class:	**B**
Efficiency 50%:	**45.0 %**
Efficiency 75%:	**54.1 %**
Efficiency 100%:	**59.1 %**
Torque:	**0.83 N.m**
Tstarting/Tnominal:	**C**
Istarting/Inominal:	**3.5**
Tmaximum/Tnominal:	**2.4**
Noise:	**64 Db(A)**
Weight:	**3.8 Kg**
Bearing DE:	**6201 2Z C3**
Bearing NDE:	**6201 2Z C3**

Regime - S1 **Altitude - 1000m** **Environment Temperature - 40ºC**

* References applied only in the UK

CONTACTS:
Universal Motors UK, Ltd
Unit E2, Meltham Mills Industrial Estate, Meltham Mills Road, Meltham, Holmfirth
West Yorkshire HD9 4AR, U.K
Tel: +44(0) 1484 660 222
Fax: +44(0) 1484 660 333
Mail: enquiries@universalmotors-group.co.uk

Universal Motors