

Product data sheet

NP

Low backlash planetary gearbox



Gearbox data	
Designation: NP025S-MF1-3-0D1-1S	
Gearbox type	NP
Gearbox size	025
Design keyword	Standard
Gearbox variation	Motor attachment gearbox
Gearbox stages	1
Gearbox ratio i	3
Output design	Smooth shaft
Clamping hub diameter	16 mm
Gearbox backlash	Standard
Gearbox material number	10033079

Motor mounting parts (included in delivery)	
Incl. mounting parts for servo motor	Rockwell MPL-B330P
Adapter plate	10051569

Order designation	
NP025S-MF1-3-0D1-1S / Rockwell MPL-B330P	

Technical specifications		
Max. output torque (Depending on the specific boundary conditions of the application)	$T_{2\alpha}$	128 Nm
Max. acceleration torque (max. 1000 cycles per hour)	T_{2B}	80 Nm
Nominal output torque (with n_{IN})	T_{2N}	40 Nm
Emergency stop torque (permitted 1000 times during the service life of the gearbox)	T_{2Not}	153 Nm
Nominal input speed (with T_{2N} and 20°C ambient temperature) ^{a)}	n_{1N}	3100 min ⁻¹
Max. input speed	n_{1Max}	7000 min ⁻¹
Mean no load running torque (with $n_1=3000$ min ⁻¹ and 20°C gearbox temp.) ^{b)}	T_{012}	0.38 Nm
Max. torsional backlash	j_t	≤ 8 arcmin
Torsional rigidity ^{b)}	C_{t21}	9.5 Nm/arcmin
Tilting rigidity	C_{2K}	24 Nm/arcmin
Max. axial force ^{c)}	F_{2AMax}	1900 N
Max. radial force ^{c)}	F_{2RMax}	2800 N
Max. tilting moment	M_{2KMax}	137 Nm
Efficiency at full load	η	97 %
Service life (for calculation, see the Chapter "Information" in our product catalogue)	L_h	> 20000 h
Weight incl. standard adapter plate	m	3.8 kg
Operating noise (with $n_1=3000$ min ⁻¹ no load)	L_{PA}	≤ 66 dB(A)
Max. permitted housing temperature		90 °C
Ambient temperature		-15 °C to 40 °C
Lubrication		lubricated for life
Paint		Dark pearl gray / innovation blue
Protection class		IP 64
Inertia (relates to the drive)	J_1	0.71 kgcm ²

- a) For higher ambient temperatures, please reduce input speed
b) Depends on clamping hub diameter
c) Refers to center of the output shaft or flange