



aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



MC Drives

Low Voltage Mobile Drives for Induction Motors
24 to 96 VDC



ENGINEERING YOUR SUCCESS.



WARNING – USER RESPONSIBILITY

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

- This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise.
- The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors.
- To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems.

Overview 5

Product Details 6

Technical Data 7

Dimensions 8

Related Products 9

 CFR - Low voltage induction motors for mobile applications..... 9

 Electro-Hydraulic Pumps (EHP) 9

Order Code..... 10

Parker Hannifin

The global leader in motion and control technologies

A world class player on a local stage

Global Product Design

Parker Hannifin has more than 40 years experience in the design and manufacturing of drives, controls, motors and mechanical products. With dedicated global product development teams, Parker draws on industry-leading technological leadership and experience from engineering teams in Europe, North America and Asia.

Local Application Expertise

Parker has local engineering resources committed to adapting and applying our current products and technologies to best fit our customers' needs.

Manufacturing to Meet Our Customers' Needs

Parker is committed to meeting the increasing service demands that our customers require to succeed in the global industrial market. Parker's manufacturing teams seek continuous improvement through the implementation of lean manufacturing methods throughout the process. We measure ourselves on meeting our customers' expectations of quality and delivery, not just our own. In order to meet these expectations, Parker operates and continues to invest in our manufacturing facilities in Europe, North America and Asia.

Electromechanical Worldwide Manufacturing Locations

Europe

Littlehampton, United Kingdom
Dijon, France
Offenburg, Germany
Filderstadt, Germany
Milan, Italy

Asia

Wuxi, China
Chennai, India

North America

Rohnert Park, California
Irwin, Pennsylvania
Charlotte, North Carolina
New Ulm, Minnesota



Offenburg, Germany

Local Manufacturing and Support in Europe

Parker provides sales assistance and local technical support through a network of dedicated sales teams and authorized technical distributors throughout Europe.


For contact information, please refer to the Sales Offices on the back cover of this document or visit www.parker.com



Milan, Italy



Littlehampton, UK



- Electromechanical Manufacturing
- Parker Sales Offices
- Distributors



Dijon, France

Low Voltage Mobile Drives for Induction Motors - MC Drives

Overview

Description

Parker MC series represents the latest design standards for compact and reliable controllers for mobile applications.

Providing a motor control solution for battery systems between 24 and 96 VDC, the MC motor controllers provide OEMs with a superb combination of power, performance and functionality.

The compact dimensions and high efficiency of this controller make integration into very tight spaces a reality without sacrificing output performance. It's design has been optimized to produce the lowest possible installed cost, whilst still maintaining superior reliability even in the most demanding of applications.



Product Features

- Advanced field oriented vector control
- Auto-configuration of typical induction motors
- Customization possible (firmware)
- High efficiency cold plate heat sink design
- IP65 protection class
- Motor temperature sensor input
- Encoder supply output (5 V)
- AB encoder input
- Dual, configurable throttle inputs
- Configurable CAN communication
- Parker IQAN compatible
- Ability to control vehicle control tasks separately from motor control
- 5 configurable coil drive outputs
- 2 configurable digital outputs
- 2 Analogue inputs / 6 Digital inputs
- Powerful MC configuration utility for system design and diagnostics
- Safety Interlock relay for battery connection

Applications

- Utility vehicles
- handling equipment, handling gantries
- Refuse Truck
- Bus and Coach
- City van
- Turf care
- Street sweepers
- Other hydraulic pump control

Technical characteristics - overview

Model	MC
Motor type	AC induction
Nominal voltage	24/96 VDC
Max 2 min current	800 Arms
Max 2 min power	60.6 kVA
Switching freq (induction)	10 kHz
Operating temperature	-40 °C to 50 °C
Storage temperature	-40 °C to 95 °C
Protection	IP65
Control type	Speed or Torque control for Induction (for PMAC, consult your local Parker sales office)
Feedback	Quadrature encoder (closed loop speed control)
Communications	CANopen, RS232/485 serial
Cooling	Air-cooled
Certifications	UL recognized component per UL583, EMC: designed to EN12895, Safety: designed to EN1175, CE marked to EN 61800-5-1 (Safety, Low Voltage Directive)

Product Details

Thanks to an IP65 protection class, the drive can be direct vehicle mounted without an enclosure.
(no direct high pressure spray)

Battery connections

U-V-W Motor connections

High efficiency cold plate heat sink design

Heat sink is sized to support 2 min. of peak current


Gore vent area to avoid condensing
Higher reliability in harsh conditions.

Single automotive rated Tyco connector for drive connections

Software

MC Configuration Manager Software


- The unique Auto-Tune function allows quick and easy characterization of the moto
- PC-based programming
- System monitoring
- System diagnostics
- Adjust system variables and programmable parameters
- Online or offline use
- Windows XP/Vista/7 compatible
- Includes USB adaptor



Software and connecting devices are required as shown here.

Programming station

MC drive



Additional Accessories

Please consult your local Parker sales office for information on additional accessories required

for the integration of MC Series inverters into vehicle systems. Accessories include contactors,

feedback devices and connection cables and mounting hardware.

Technical Data

Part number	Switching frequency	Max Output frequency	Rms output 1 hour Current A	Rms output 2 min current A	Nominal Input Voltage V
MCC-02-0180-01-02	10kHz	300Hz ¹	90	180	24
MCC-02-0250-01-02			125	250	24
MCC-04-0200-01-02			100	200	36-48
MCC-08-0175-01-02			80	175	48-80
MCD-02-0350-01-02			175	350	24
MCD-04-0275-01-02			140	275	36-48
MCD-04-0350-01-02			175	350	36-48
MCD-08-0250-01-02			110	250	48-80
MCE-03-0400-01-02			175	400	24-36
MCE-03-0500-01-02			240	500	24-36
MCE-04-0450-01-02			205	450	36-48
MCE-04-0550-01-02			250	550	36-48
MCE-08-0350-01-02			100	350 (1 min)	48-80
MCF-03-0650-01-02			300	650	24-36
MCF-03-0800-01-02			355	800	24-36
MCF-04-0650-01-02			295	650	36-48
MCF-08-0450-01-02			155	450	48-80
MCF-08-0550-01-02			190	550	48-80
MCF-08-0650-01-02			195	650 (1 min)	48-80
MCF-09-0550-01-02			175	550	72-96
MCF-09-0650-01-02			200	650	72-96


Notes: All current ratings are rms values per motor phase.

Continuous current for design life is the maximum long-term current, at an internal heatsink long-term temperature of 70 °C (158 °F), at which the controller will achieve its design life (20,000 h for 24 ... 80 V). Note that much higher 1 h ratings can be achieved with additional heatsinking.


¹ 300 Hz with induction-only software, OS20-OS22.

Dimensions


MC C




MC E



MC D



MC F



Dimensions [mm]

Related Products

CFR - Low voltage induction motors for mobile applications

Description

This range of AC induction motors has been specifically developed for battery-operated vehicles. These low cost air-cooled induction motors (ACIM) are automatically recognised by the MC drives. Typically adapted for Electro-Hydraulic Pumps (EHP), the Parker's product support team will work with pump division to coordinate mechanical solution.

Product Features

- Ruggedised low voltage induction motor
- Speed up to 3500 rpm
- Power up to 40 kW
- Torque up to 150 Nm
- IP rating: IP20 to IP65
- Built-in thermal sensor for monitoring motor temperature
- Customisation possibilities (shaft, flange, additional fan if required)

Typical applications

- Electric power steering
- Electro-Hydraulic pump for small power hydraulic cylinders



Electro-Hydraulic Pumps (EHP)

Subsystem capabilities

Parker offers pre-engineered and customisable EHP to assist in the development of hybrid-electric vehicle platforms. The EHP kit will include a low voltage MC drive + AC induction motor + hydraulic pump - fixed displacement (vane or gear style) or variable displacement (bent-axis piston style)

Please consult your local sales office to discuss your specific application requirements.



Order Code

	1	2	3		4		5		6		7
Order example	M	C	C	-	04	-	0450	-	01	-	00

1 Inverter family	0650	650 A - MC Series Frame F
M Mobile Inverter		
2 Control module build	6	Branding
C Low Voltage - 24, 48, 80 VDC	01	Parker branded
3 Frame size	7	Special options
C	00	E Version with PMAC
D MC Series	02	E Version without PMAC
E		
F		
4 Maximum operating voltage		
Low Voltage MC Series Inverter		
02 24 VDC		
03 36 VDC		
04 48 VDC		
08 80 VDC		
09 96 VDC		
5 Peak current ratings		
24 VDC Nominal Voltage		
0180 180 A - MC Series Frame C		
0250 250 A - MC Series Frame C		
0350 350 A - MC Series Frame D		
36 VDC Nominal Voltage		
0400 400 A - MC Series Frame E		
0500 500 A - MC Series Frame E		
0650 650 A - MC Series Frame F		
0800 800 A - MC Series Frame E		
48 VDC Nominal Voltage		
0200 200 A - MC Series Frame C		
0275 275 A - MC Series Frame D		
0350 350 A - MC Series Frame D		
0450 450 A - MC Series Frame E		
0450 450 A - MC Series Frame F		
0550 550 A - MC Series Frame E		
0650 650 A - MC Series Frame F		
80 VDC Nominal Voltage		
0175 175 A - MC Series Frame C		
0250 250 A - MC Series Frame D		
0350 350 A - MC Series Frame E		
0450 450 A - MC Series Frame F		
0550 550 A - MC Series Frame F		
0650 650 A - MC Series Frame F		
96 VDC Nominal Voltage		
0550 550 A - MC Series Frame F		



Parker's Motion & Control Technologies

At Parker, we're guided by a relentless drive to help our customers become more productive and achieve higher levels of profitability by engineering the best systems for their requirements. It means looking at customer applications from many angles to find new ways to create value. Whatever the motion and control technology need, Parker has the experience, breadth of product and global reach to consistently deliver. No company knows more about motion and control technology than Parker. For further info call 00800 27 27 5374



Aerospace

Key Markets

Aftermarket services
Commercial transports
Engines
General & business aviation
Helicopters
Launch vehicles
Military aircraft
Missiles
Power generation
Regional transports
Unmanned aerial vehicles

Key Products

Control systems & actuation products
Engine systems & components
Fluid conveyance systems & components
Fluid metering, delivery & atomization devices
Fuel systems & components
Fuel tank inerting systems
Hydraulic systems & components
Thermal management
Wheels & brakes



Climate Control

Key Markets

Agriculture
Air conditioning
Construction Machinery
Food & beverage
Industrial machinery
Life sciences
Oil & gas
Precision cooling
Process
Refrigeration
Transportation

Key Products

Accumulators
Advanced actuators
CO₂ controls
Electronic controllers
Filter driers
Hand shut-off valves
Heat exchangers
Hose & fittings
Pressure regulating valves
Refrigerant distributors
Safety relief valves
Smart pumps
Solenoid valves
Thermostatic expansion valves



Electromechanical

Key Markets

Aerospace
Factory automation
Life science & medical
Machine tools
Packaging machinery
Paper machinery
Plastics machinery & converting
Primary metals
Semiconductor & electronics
Textile
Wire & cable

Key Products

AC/DC drives & systems
Electric actuators, gantry robots & slides
Electrohydraulic actuation systems
Electromechanical actuation systems
Human machine interface
Linear motors
Stepper motors, servo motors, drives & controls
Structural extrusions



Filtration

Key Markets

Aerospace
Food & beverage
Industrial plant & equipment
Life sciences
Marine
Mobile equipment
Oil & gas
Power generation & renewable energy
Process
Transportation
Water Purification

Key Products

Analytical gas generators
Compressed air filters & dryers
Engine air, coolant, fuel & oil filtration systems
Fluid condition monitoring systems
Hydraulic & lubrication filters
Hydrogen, nitrogen & zero air generators
Instrumentation filters
Membrane & fiber filters
Microfiltration
Sterile air filtration
Water desalination & purification filters & systems



Fluid & Gas Handling

Key Markets

Aerial lift
Agriculture
Bulk chemical handling
Construction machinery
Food & beverage
Fuel & gas delivery
Industrial machinery
Life sciences
Marine
Mining
Mobile
Oil & gas
Renewable energy
Transportation

Key Products

Check valves
Connectors for low pressure fluid conveyance
Deep sea umbilicals
Diagnostic equipment
Hose couplings
Industrial hose
Mooring systems & power cables
PTFE hose & tubing
Quick couplings
Rubber & thermoplastic hose
Tube fittings & adapters
Tubing & plastic fittings



Hydraulics

Key Markets

Aerial lift
Agriculture
Alternative energy
Construction machinery
Forestry
Industrial machinery
Machine tools
Marine
Material handling
Mining
Oil & gas
Power generation
Refuse vehicles
Renewable energy
Truck hydraulics
Turf equipment

Key Products

Accumulators
Cartridge valves
Electrohydraulic actuators
Human machine interfaces
Hybrid drives
Hydraulic cylinders
Hydraulic motors & pumps
Hydraulic systems
Hydraulic valves & controls
Hydrostatic steering
Integrated hydraulic circuits
Power take-offs
Power units
Rotary actuators
Sensors



Pneumatics

Key Markets

Aerospace
Conveyor & material handling
Factory automation
Life science & medical
Machine tools
Packaging machinery
Transportation & automotive

Key Products

Air preparation
Brass fittings & valves
Manifolds
Pneumatic accessories
Pneumatic actuators & grippers
Pneumatic valves & controls
Quick disconnects
Rotary actuators
Rubber & thermoplastic hose & couplings
Structural extrusions
Thermoplastic tubing & fittings
Vacuum generators, cups & sensors



Process Control

Key Markets

Alternative fuels
Biopharmaceuticals
Chemical & refining
Food & beverage
Marine & shipbuilding
Medical & dental
Microelectronics
Nuclear Power
Offshore oil exploration
Oil & gas
Pharmaceuticals
Power generation
Pulp & paper
Steel
Water/wastewater

Key Products

Analytical Instruments
Analytical sample conditioning products & systems
Chemical injection fittings & valves
Fluoropolymer chemical delivery fittings, valves & pumps
High purity gas delivery fittings, valves, regulators & digital flow controllers
Industrial mass flow meters/controllers
Permanent no-weld tube fittings
Precision industrial regulators & flow controllers
Process control double block & bleeds
Process control fittings, valves, regulators & manifold valves



Sealing & Shielding

Key Markets

Aerospace
Chemical processing
Consumer
Fluid power
General Industrial
Information technology
Life sciences
Microelectronics
Military
Oil & gas
Power generation
Renewable energy
Telecommunications
Transportation

Key Products

Dynamic seals
Elastomeric o-rings
Electro-medical instrument design & assembly
EMI shielding
Extruded & precision-cut, fabricated elastomeric seals
High temperature metal seals
Homogeneous & inserted elastomeric shapes
Medical device fabrication & assembly
Metal & plastic retained composite seals
Shielded optical windows
Silicone tubing & extrusions
Thermal management
Vibration dampening

Parker Worldwide

Europe, Middle East, Africa

AE – United Arab Emirates, Dubai
Tel: +971 4 8127100
parker.me@parker.com

AT – Austria, Wiener Neustadt
Tel: +43 (0)2622 23501-0
parker.austria@parker.com

AT – Eastern Europe, Wiener Neustadt
Tel: +43 (0)2622 23501 900
parker.easteurope@parker.com

AZ – Azerbaijan, Baku
Tel: +994 50 2233 458
parker.azerbaijan@parker.com

BE/LU – Belgium, Nivelles
Tel: +32 (0)67 280 900
parker.belgium@parker.com

BG – Bulgaria, Sofia
Tel: +359 2 980 1344
parker.bulgaria@parker.com

BY – Belarus, Minsk
Tel: +375 17 209 9399
parker.belarus@parker.com

CH – Switzerland, Etoy
Tel: +41 (0)21 821 87 00
parker.switzerland@parker.com

CZ – Czech Republic, Klecany
Tel: +420 284 083 111
parker.czechrepublic@parker.com

DE – Germany, Kaarst
Tel: +49 (0)2131 4016 0
parker.germany@parker.com

DK – Denmark, Ballerup
Tel: +45 43 56 04 00
parker.denmark@parker.com

ES – Spain, Madrid
Tel: +34 902 330 001
parker.spain@parker.com

FI – Finland, Vantaa
Tel: +358 (0)20 753 2500
parker.finland@parker.com

FR – France, Contamine s/Arve
Tel: +33 (0)4 50 25 80 25
parker.france@parker.com

GR – Greece, Athens
Tel: +30 210 933 6450
parker.greece@parker.com

HU – Hungary, Budaörs
Tel: +36 23 885 470
parker.hungary@parker.com

IE – Ireland, Dublin
Tel: +353 (0)1 466 6370
parker.ireland@parker.com

IT – Italy, Corsico (MI)
Tel: +39 02 45 19 21
parker.italy@parker.com

KZ – Kazakhstan, Almaty
Tel: +7 7273 561 000
parker.easteurope@parker.com

NL – The Netherlands, Oldenzaal
Tel: +31 (0)541 585 000
parker.nl@parker.com

NO – Norway, Asker
Tel: +47 66 75 34 00
parker.norway@parker.com

PL – Poland, Warsaw
Tel: +48 (0)22 573 24 00
parker.poland@parker.com

PT – Portugal, Leca da Palmeira
Tel: +351 22 999 7360
parker.portugal@parker.com

RO – Romania, Bucharest
Tel: +40 21 252 1382
parker.romania@parker.com

RU – Russia, Moscow
Tel: +7 495 645-2156
parker.russia@parker.com

SE – Sweden, Spånga
Tel: +46 (0)8 59 79 50 00
parker.sweden@parker.com

SK – Slovakia, Banská Bystrica
Tel: +421 484 162 252
parker.slovakia@parker.com

SL – Slovenia, Novo Mesto
Tel: +386 7 337 6650
parker.slovenia@parker.com

TR – Turkey, Istanbul
Tel: +90 216 4997081
parker.turkey@parker.com

UA – Ukraine, Kiev
Tel: +380 44 494 2731
parker.ukraine@parker.com

UK – United Kingdom, Warwick
Tel: +44 (0)1926 317 878
parker.uk@parker.com

ZA – South Africa, Kempton Park
Tel: +27 (0)11 961 0700
parker.southafrica@parker.com

North America

CA – Canada, Milton, Ontario
Tel: +1 905 693 3000

US – USA, Cleveland
Tel: +1 216 896 3000

Asia Pacific

AU – Australia, Castle Hill
Tel: +61 (0)2-9634 7777

CN – China, Shanghai
Tel: +86 21 2899 5000

HK – Hong Kong
Tel: +852 2428 8008

IN – India, Mumbai
Tel: +91 22 6513 7081-85

JP – Japan, Tokyo
Tel: +81 (0)3 6408 3901

KR – South Korea, Seoul
Tel: +82 2 559 0400

MY – Malaysia, Shah Alam
Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington
Tel: +64 9 574 1744

SG – Singapore
Tel: +65 6887 6300

TH – Thailand, Bangkok
Tel: +662 186 7000-99

TW – Taiwan, Taipei
Tel: +886 2 2298 8987

South America

AR – Argentina, Buenos Aires
Tel: +54 3327 44 4129

BR – Brazil, Sao Jose dos Campos
Tel: +55 800 727 5374

CL – Chile, Santiago
Tel: +56 2 623 1216

MX – Mexico, Toluca
Tel: +52 72 2275 4200

We reserve the right to make technical changes. The data correspond to the technical state at the time of printing.
© 2013 Parker Hannifin Corporation.
All rights reserved.

192-300107N2

January 2014



EMEA Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

US Product Information Centre

Toll-free number: 1-800-27 27 537

www.parker.com

Your local authorized Parker distributor