

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhaltes sind nur mit unserer Zustimmung gestattet. Alle Rechte vorbehalten.
Passing on as well as duplication of this document, utilization and report of their contents are permitted only with our agreement. All rights reserved.

Dimension drawing:

Label





Errors and changes reserved.

Mechanical Data:


Length L1	300,0 mm	**Fixing space N1**	224,0 mm	**total weight**	36,0 kg	
Width B1	180,0 mm	**Fixing space N2**	125,0 mm	**Weight Al**	3,0 kg	
Height H1	270,0 mm	**Diameter D1**	10 x 18 mm	**Weight Cu**	1,30 kg	
		Diameter D2	ø11 mm			
				connection	30 x 4/ø 11	
		Length A1	39,0 mm	**PE**	M12	

Tolerance according to ISO2768-1 Tolerance class c

Electrical Data:

Rated current:	I eff.	250 A	
linear up:		275 A	
Voltage:	U	3x 500 V	(50 / 60 Hz)
Inductance:	L	0,118 mH	± 10 %
DC resistance:	R	0,68mOhm	± 10 %
Voltage drop:		uk 4%	@ 400V/ 50Hz
		uk 4%	@ 480V/ 60Hz
Power losses:		254,0 W	
cooling system		AN	
Thermal class:		F	@ 40° C Environment
Climate class:		25/085/21	DIN IEC 68 Part 1
Max. Winding temp:		140° C	Environment +Δϑ
Degree of protection:		IP 00	

Schematic:




Tests

Inductance (mH)	Lo (± 10%)	bei 100Hz , 1V
High voltage	2,5 kV /50 Hz/ 60s	Winding - Winding
	2,5 kV /50 Hz/ 60s	Winding - PE
mechan. dimensions	yes	
Visual inspection	yes	

Label:

Designation:	REO 3ph-line choke
Text 1:	N CNW 903 /250/0,118/500/50
I[A] :	250
U[V]	500
L[mH]	0,118
Text 2:	AN
Text 3:	T40/F
Terminal designation:	1 2 3 4 5 6



Cond.	Date	Name	Amendment	Page No. off	No.
	Date	Name			
signed					
revised by	13.5.19	Scha.			
checked	13.5.19	Bo			

Designation:

REO 3ph-line choke

N CNW 903 /250/0,118/500/50

Drawing-Nr.:

BV 969326.20-00