

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhaltes sind nur mit unserer Zustimmung gestattet. Alle Rechte vorbehalten.
Passing on as well as duplication of this document, utilization and report of their contents are permitted only with our agreement. All rights reserved.

Dimension drawing:

RoHS 2011/65/EU





Errors and changes reserved.

Mechanical Data:


Length L1	340,0 mm	**Fixing space N1**	248,0 mm	**total weight**	45,0 kg
Width B1	192,0 mm	**Fixing space N2**	130,0 mm	**Weight Al**	5,0 kg
Height H1	305,0 mm	**Diameter D1**	10 x 18 mm	**Weight Cu**	2,60 kg
		Diameter D2	ø13 mm		
				connection	40 x 5/ø 13
		Length A1	49,0 mm	**PE**	M12

Tolerance according to ISO2768-1 Tolerance class c

Electrical Data:

Rated current:	I eff.	350 A	
linear up:		385 A	
Voltage:	U	3x 500 V	(50 / 60 Hz)
Inductance:	L	0,084 mH	± 10 %
DC resistance:	R	0,305mOhm	± 10 %
Voltage drop:		uk 4%	@ 400V/50Hz
		uk 4%	@ 480V/60Hz
Power losses:		267,0 W	
cooling system		AN	
Thermal class:		F	@ 40° C Environment
Climate class:		25/085/21	DIN IEC 68 Part 1
Max. Winding temp:		140° C	Environment +Δϑ
Degree of protection:		IP 00	

Schematic:




Tests

Inductance (mH)	Lo (± 10%)	bei 100Hz , 1V
High voltage	2,5 kV /50 Hz/ 60s	Winding - Winding
	2,5 kV /50 Hz/ 60s	Winding - PE
mechan. dimensions	yes	
Visual inspection	yes	

Label:

Designation:	REO 3ph-line choke
Text 1:	N CNW 903 /350/0,084/500/50
I[A] :	350
U[V]	500
L[mH]	0,084
Text 2:	AN
Text 3:	T40/F
Terminal designation:	1 2 3 4 5 6



Cond.	Date	Name	Amendment
	Date	Name	Page No. off No.
signed			
revised by	08.05.19	Scha.	
checked	10.05.19	Fr.	

Designation:

REO 3ph-line choke

N CNW 903 /350/0,084/500/50

Drawing-Nr.:

BV 969328.20-00