



## Ordering and shipping details

|                       |                             |
|-----------------------|-----------------------------|
| Category              | 22205 - ATV630 FRAMES 1 & 2 |
| Discount Schedule     | CP4E                        |
| GTIN                  | 00785901691730              |
| Nbr. of units in pkg. | 1                           |
| Package weight(Lbs)   | 0.7700000000000002          |
| Returnability         | Y                           |
| Country of origin     | CN                          |

## Main

|                                       |   |
|---------------------------------------|---|
| Accessory / separate part category    | Communication accessory   |
| Accessory / separate part type        | Wireless access point   |
| Accessory / separate part destination | PC<br>PLC<br>Variable speed drive<br>Smart phone<br>Tablet<br>Phablet |

## Complementary

|                     |  |
|---------------------|--|
| Range compatibility | Modicon M251<br>Modicon M580<br>Altivar Process ATV600<br>Altivar Process ATV900 |
| Kit composition     | USB cable<br>Battery<br>Quick start guide<br>Power adaptor<br>Ethernet cable     |
| Function available  | Automatic detection of Schneider-Electric products and other devices on Ethernet |

|                             |   |
|-----------------------------|---|
| Type of connector           | Micro USB type A female<br>Female RJ45 automatic negotiation of 10/100 Mbit/s   |
| Communication port protocol | DHCP<br>Ethernet TCP/IP<br>ICMP<br>PPPoE (Point-to-Point Protocol over Ethernet)  |
| Method of access            | CSMA/CA<br>CSMA/CD  |
| Operating system            | Windows Vista<br>Windows XP<br>Windows 7<br>Windows 8<br>Android<br>Mac iOS   |
| System requirements         | Microsoft internet explorer<br>Apple Safari<br>Firefox<br>Google Chrome   |
| Supply                      | Rechargeable internal battery   |
| Local signalling            | 1 LED green, orange and red battery status<br>1 LED scan status<br>1 LED Ethernet port activity<br>1 LED wireless function status |
| Product weight              | 0.77 lb(US) (0.35 kg)   |

## Environment

|                                       |  |
|---------------------------------------|--|
| IP degree of protection               | IP20   |
| Ambient air temperature for operation | 32...104 °F (0...40 °C)  |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)   |
| Relative humidity                     | 5...90 % for storage, without condensation conforming to IEC 60068-2-3<br>10...90 % Operation , Without condensation conforming to IEC 60068-2-3 |
| Standards                             | IEEE 802.3<br>IEEE 802.3u<br>IEEE 802.3x<br>IEEE 802.11b<br>IEEE 802.11g<br>IEEE 802.11n<br>IEEE 802.1x  |
| Product certifications                | CE<br>FCC  |