Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3094B **SIMOTICS GP - 90 L - IM B35 - 4p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	1.50	-/-	5.50	1445	9.9	85.3	85.7	84.4	0.80	0.73	0.60	7.3	2.9	3.5	IE3
400	Y	50	1.50	-/-	3.15	1445	9.9	85.3	85.7	84.4	0.80	0.73	0.60	7.3	2.9	3.5	IE3
460	Y	60	1.75	-/-	3.15	1740	9.6	86.5	86.7	85.4	0.80	0.74	0.62	7.7	2.9	3.7	IE3
460	Y	60	1.50	-/-	2.85	1755	8.2	86.5	86.6	84.7	0.77	0.69	0.57	8.6	3.4	4.3	IE3
IM B35 / IM 2001			FS 90 L			IP55		IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 17.6 s | 21.8 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	56 / 68 dB(A) 2)	58 / 70 dB(A) 2)	Vibration severity grade	A
Moment of inertia	0.0049 kg m²		Thermal class	F
Bearing DE | NDE	6205 2Z C3	6004 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	19 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*	Link documents
DI MC LVM		DT Configurator			

SIEMENS

document type	document status
datasheet	released
title: **1LE1003-0EB42-2JA4-Z** **H01**	document number

rev.	creation date	language	Page
01	2022-04-20	en	1/2

© Siemens AG 2022

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3094B **SIMOTICS GP - 90 L - IM B35 - 4p**

Special design

H01	Bolted on mounting feet (instead of cast)

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*	Link documents	
SIEMENS	document type datasheet			document status released		
	title 1LE1003-0EB42-2JA4-Z			document number		
© Siemens AG 2022	H01			rev. 01	creation date 2022-04-20	language en	Page 2/2