Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3104B **SIMOTICS GP - 100 L - IM B35 - 4p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	2.20	-/-	7.80	1455	14.4	86.7	87.2	86.3	0.82	0.76	0.64	8.3	3.0	3.8	IE3
400	Y	50	2.20	-/-	4.45	1455	14.4	86.7	87.2	86.3	0.82	0.76	0.64	8.3	3.0	3.8	IE3
460	Y	60	2.54	-/-	4.30	1750	13.9	89.5	90.1	89.2	0.83	0.77	0.66	8.8	3.0	3.9	IE3
460	Y	60	2.20	-/-	3.85	1760	11.9	89.5	89.5	88.0	0.80	0.73	0.61	9.9	3.5	4.6	IE3
IM B35 / IM 2001			FS 100 L			IP55		IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 18.6 s | 22.6 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	60 / 72 dB(A) 2)	62 / 74 dB(A) 2)	Vibration severity grade	A
Moment of inertia	0.0101 kg m²		Thermal class	F
Bearing DE | NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	25 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*	Link documents
DI MC LVM		DT Configurator			

SIEMENS

document type	document status
datasheet	released
title: **1LE1003-1AB42-2JA4-Z** **H01**	document number

rev.	creation date	language	Page
01	2022-04-20	en	1/2

© Siemens AG 2022

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3104B **SIMOTICS GP - 100 L - IM B35 - 4p**

Special design

H01	Bolted on mounting feet (instead of cast)

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*		Link documents
SIEMENS	document type datasheet			document status released		
	title 1LE1003-1AB42-2JA4-Z			document number		
© Siemens AG 2022	H01			rev. 01	creation date 2022-04-20	language en / Page 2/2