MOTOR DATA SHEET

MOTOR PART CODE: 7.523TECA-IE3-230V

Model **T3A 132S2-2**

Housing material		Aluminum
Phase		Three
Frame size		132
Power(50Hz)	kW	7.50
Current(A)230V	Δ	22.62
Current(A)400V	Y	13.06
Speed(50Hz)	(r/min)	2930
Efficiency	IE3	
	Eff.100%	90.10
	Eff.75%	90.90
	Eff.50%	90.70
Power factor cosφ	100% load	0.92
60Hz 265/460V	Power(kW)	8.63
60Hz 276/480V	Power(kW)	9.00
Speed(60Hz)	(r/min)	3520
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitute		1000 m above sea level

Rated torque(N.m)	24.45
Tst/Tn (Times)	2.6
Tmax/Tn (Times)	3.6
Tmin/Tn (Times)	1.9
Ist/In (Times)	10.1
Bearings type(DE)	6308-2RZ
Bearings type(NDE)	6208-2RZ
Oil seals	40x58x7
Cable glands	2-M25*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	PTC130°C
Rotation direction	BI-DIRECTIONAL
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	80
Net weight(kg)	51.70
Moment of inertia（kg*m²）	0.018996070

TEC Electric Motors Ltd, 291-296 Oak Drive, Hartlebury Trading Est, Kidderminster, Worcs, DY10 4JB
T: 01299 252 990 F: 01299 253 597 www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information