MOTOR SPECIFICATION SHEET

SPECIFIC N°: OD090L4H2305P4

MOTOR PART NR	OD090L4H2305P4	CUSTOMER PART NR		
DRAWING NR	OD090L4H2305P4	MOTOR TYPE	OD090L42305P4	
Type of winding	3 PHASE SINGLE WINDING 6 LEADS			
PROTECTION	II 2G Ex d IIC T4 Gb	CERTIFICATE	EUM1 10 ATEX 0350	
IP PROTECTION	IP66	ENVIRONMENT CONDITIONS	-20 /+55°C Max Altitude: 1000m	
POLES	4	NOMINAL POWER kW	1,5 1,8	
Nom. Speed rpm	1415 1700	Voltage-Frequency	230/400V 50Hz 265/460V 60Hz	Tolerance: Voltage ±5%
Nom. Current A	6.6/3.8 6.6/3.8	COS ϕ	0.78 0.78	
Duty	S1 Continuous Duty	Direction of Rotation	BIDIRECTIONAL	
Insulation Class	F	Mounting IM	B3	
IEC Frame Size	90L	Material end Shield/Flange	Aluminium	
Material Terminal Box	Aluminium	Material Fan	PLASTIC Nylon V6	
Material Cover Fan	Zinc plated steel	Material shaft	Steel C43	
DE Bearing Type	6205-ZZ	NDE Bearing Type	6205-ZZ	
Position of terminal box	TOP	Cable gland Type	1XM20	
Cable gland position (view from DE)	Right	Motor Colour	Not painted motor	
Painting	-	Thermal protection	-	
Special	-		-	


In compliance with the EC Directives

94/9/EC (ATEX)
2004/108/EC (EMC)
2006/42/EC (Machinery)
2002/95/EC (RoHS)

and comply with the following Standards

EN 60079-0, 1
EN 60034-1,2,5,6,7,9,12,14,
IEC60072-1,
EN 60259

Overall dimensions



La **ELPROMtech S.r.l.** si riserva a termini di legge la proprietà del documento con divieto di riprodurlo o di renderlo comunque noto a terzi o a ditte concorrenti, senza la sua autorizzazione.