

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer		: IDS	
Product line		: W22 IE3 Three-Phase	Product code : 12862395
Frame	: 180M	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 22 kW	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 400/690 V	Altitude	: 1000 m.a.s.l.
Rated current	: 39.7/23.0 A	Protection degree	: IP55
L. R. Amperes	: 330/191 A	Cooling method	: IC411 - TEFC
LRC	: 8.3	Mounting	: B3T
No load current	: 16.9/9.81 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 2950 rpm	Noise level ²	: 67.0 dB(A)
Slip	: 1.67 %	Starting method	: Direct On Line
Rated torque	: 7.26 kgfm	Approx. weight ³	: 169 kg
Locked rotor torque	: 270 %		
Breakdown torque	: 360 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 0.0968 kgm ²		
Design	: N		
Output	50%	75%	100%
Efficiency (%)	92.3	93.0	92.9
Power Factor	0.69	0.80	0.86
Foundation loads			
Max. traction		: 270 kgf	
Max. compression		: 438 kgf	
		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6311 C3	6211 Z C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	17000 h	20000 h
Lubricant amount	:	18 g	11 g
Lubricant type	:	Mobil Polyrex EM	
Notes			
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>			
<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.</p>			
Rev.	Changes Summary		Performed
			Checked
			Date
Performed by			
Checked by			
Date	25/06/2019		
		Page	Revision
		1 / 3	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : IDS

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 3	
Date	25/06/2019				

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : IDS

Product line : W22 IE3 Three-Phase

Product code : 12862395



Performance : 400/690 V 50 Hz 2P

Rated current : 39.7/23.0 A
 LRC : 8.3
 Rated torque : 7.26 kgfm
 Locked rotor torque : 270 %
 Breakdown torque : 360 %
 Rated speed : 2950 rpm

Moment of inertia (J) : 0.0968 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		
Checked by				
Date	25/06/2019			
		Revision		