

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer		: IDS			
Product line		: W22 IE3 Three-Phase		Product code : 12862427	
Frame : 80 Output : 0.75 kW Poles : 2 Frequency : 50 Hz Rated voltage : 230/400 V Rated current : 2.83/1.63 A L. R. Amperes : 21.3/12.2 A LRC : 7.5 No load current : 1.57/0.900 A Rated speed : 2870 rpm Slip : 4.33 % Rated torque : 0.255 kgfm Locked rotor torque : 330 % Breakdown torque : 340 % Insulation class : F Service factor : 1.00 Moment of inertia (J) : 0.0008 kgm ² Design : N		Locked rotor time : 32s (cold) 18s (hot) Temperature rise : 80 K Duty cycle : S1 Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Cooling method : IC411 - TEFC Mounting : B5T Rotation ¹ : Both (CW and CCW) Noise level ² : 59.0 dB(A) Starting method : Direct On Line Approx. weight ³ : 15.0 kg			
Output	50%	75%	100%	Foundation loads	
Efficiency (%)	80.0	82.0	81.0	Max. traction : 21 kgf	
Power Factor	0.61	0.74	0.82	Max. compression : 36 kgf	
		<u>Drive end</u>		<u>Non drive end</u>	
Bearing type	:	6204 ZZ		6203 ZZ	
Sealing	:	Oil Seal		Oil Seal	
Lubrication interval	:	-		-	
Lubricant amount	:	-		-	
Lubricant type	:	Mobil Polyrex EM			
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.		
Rev.	Changes Summary			Performed	Checked
Performed by					
Checked by				Page	Revision
Date	26/06/2019			1 / 2	

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : IDS

Product line : W22 IE3 Three-Phase

Product code : 12862427



Performance : 230/400 V 50 Hz 2P

Rated current : 2.83/1.63 A
 LRC : 7.5
 Rated torque : 0.255 kgfm
 Locked rotor torque : 330 %
 Breakdown torque : 340 %
 Rated speed : 2870 rpm

Moment of inertia (J) : 0.0008 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2Revision		
Checked by				
Date	26/06/2019			