

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer		: IDS	
Product line		: W22 IE3 Three-Phase	Product code : 12862700
Frame	: L90S	Locked rotor time	: 55s (cold) 31s (hot)
Output	: 0.75 kW	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/400 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.36/1.93 A	Protection degree	: IP55
L. R. Amperes	: 17.5/10.0 A	Cooling method	: IC411 - TEFC
LRC	: 5.2	Mounting	: B3T
No load current	: 2.09/1.20 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 950 rpm	Noise level <sup>2</sup>	: 45.0 dB(A)
Slip	: 5.00 %	Starting method	: Direct On Line
Rated torque	: 0.769 kgfm	Approx. weight <sup>3</sup>	: 24.5 kg
Locked rotor torque	: 250 %		
Breakdown torque	: 280 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 0.0060 kgm <sup>2</sup>		
Design	: N		
Output	50%	75%	100%
Efficiency (%)	76.5	79.0	79.0
Power Factor	0.49	0.62	0.71
Foundation loads			
Max. traction		: 49 kgf	
Max. compression		: 73 kgf	
		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6204 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	
Notes			
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>			
<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.</p>			
Rev.	Changes Summary		Performed
			Checked
			Date
Performed by			
Checked by			
Date	27/06/2019		
		Page	Revision
		1 / 2	

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : IDS

Product line : W22 IE3 Three-Phase

Product code : 12862700



Performance : 230/400 V 50 Hz 6P

Rated current : 3.36/1.93 A  
 LRC : 5.2  
 Rated torque : 0.769 kgfm  
 Locked rotor torque : 250 %  
 Breakdown torque : 280 %  
 Rated speed : 950 rpm

Moment of inertia (J) : 0.0060 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					