

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer		: IDS	
Product line		: W22 IE3 Three-Phase	Product code : 12863119
Frame	: 315S/M	Locked rotor time	: 45s (cold) 25s (hot)
Output	: 185 kW	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 400/690 V	Altitude	: 1000 m.a.s.l.
Rated current	: 327/190 A	Protection degree	: IP55
L. R. Amperes	: 2551/1479 A	Cooling method	: IC411 - TEFC
LRC	: 7.8	Mounting	: B3T
No load current	: 130/75.4 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1490 rpm	Noise level <sup>2</sup>	: 71.0 dB(A)
Slip	: 0.67 %	Starting method	: Direct On Line
Rated torque	: 121 kgfm	Approx. weight <sup>3</sup>	: 1202 kg
Locked rotor torque	: 270 %		
Breakdown torque	: 290 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 4.42 kgm <sup>2</sup>		
Design	: N		
Output	50%	75%	100%
Efficiency (%)	95.5	96.1	96.0
Power Factor	0.71	0.80	0.85
Foundation loads			
Max. traction		: 1935 kgf	
Max. compression		: 3137 kgf	
		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6319 C3	6316 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	11000 h	13000 h
Lubricant amount	:	45 g	34 g
Lubricant type	:	Mobil Polyrex EM	
Notes			
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>			
<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.</p>			
Rev.	Changes Summary		Performed
			Checked
			Date
Performed by			
Checked by			
Date	27/06/2019		
		Page	Revision
		1 / 3	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : IDS

### Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 3	
Date	27/06/2019				

# VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : IDS

Product line : W22 IE3 Three-Phase

Product code : 12863119



Performance : 400/690 V 50 Hz 4P

Rated current : 327/190 A  
 LRC : 7.8  
 Rated torque : 121 kgfm  
 Locked rotor torque : 270 %  
 Breakdown torque : 290 %  
 Rated speed : 1490 rpm

Moment of inertia (J) : 4.42 kgm<sup>2</sup>  
 Duty cycle : S1  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		
Checked by				
Date	27/06/2019			
		Revision		